


SPANN-BOX® SIZE 0

The size 0 Spann-Box® is the smallest in our range. It is used where installation spaces are very restricted. The plastic housing means there is no risk of corrosion.

DIN 8187 chain no.	Pitch in mm	Pitch in inch	Simplex	Duplex	Triplex
≤ 06B	-	-			
06B	9.525	3/8			
08B	12.7	1/2			
10B	15.875	5/8			
12B	19.05	3/4			
				Light	Heavy
Tension force			1 spring	58 – 32N	132 – 60N
			Tension distance	40mm	40mm

SPANN-BOX® SIZE 0

with semi-circular profile

Applications

- Restricted installation space
- Environments with a risk of corrosion
- Chain drives with a pitch of up to 3/4"

Tensioning pressure

- Choice of light or heavy spring force
- Lock pin in base of housing

Attachment

- Installed underneath the chain
- Bore holes in the housing

Stainless steel screws and springs



DIN 8187 chain no.	Light tension force article no.	Heavy tension force article no.	Availability
≤06B-1 (U profile)	281 000 001	281 000 002	●
08B-1	281 000 003	281 000 004	●
10B-1	281 000 003	281 000 004	●
12B-1	281 000 005	281 000 006	●
06B-2	281 000 007	281 000 008	●
08B-2	281 000 009	281 000 010	●

Special designs on request ● Stocked ○ Available within 10 days

